

RENTAL ID 3862



Hydraulic winch 15 ton

- 15 ton winch with spooling device and lifting lugs.
- Fitted with drip-free 71-series connection on our standardized hose package - set up for our HPU-series.
- Four-stage geared construction with fail safe disc brake.
- Easy to assembly with frame and bolt connection.
- Compact design
- Documentation available in our client database.

GENERAL

| | |
|-------|-------------------------------|
| Owner | KOLOS Lifting & Inspection AS |
|-------|-------------------------------|

| | |
|----------------------|-------------------------------------|
| Type, model and area | 15 ton hydraulic winch // LEVAHN 15 |
|----------------------|-------------------------------------|

CODES / APPROVALS

| | |
|-----------|----------------------------------|
| CE marked | Yes (98/37/EC // 1994-08-19-820) |
|-----------|----------------------------------|

| | |
|-------|----------|
| Other | EN 13001 |
|-------|----------|

| | |
|--------|--------------------------------|
| NORSOK | Z-015 (U99, normally unmanned) |
|--------|--------------------------------|

SPECIFICATIONS

| | |
|-----------------|-----------------------|
| Design capacity | 15T full drum lifting |
|-----------------|-----------------------|

| | |
|-------------------|----------------------------------|
| Flow and pressure | Up to 240 l/min // Up to 300 bar |
|-------------------|----------------------------------|

| | |
|---------------|--|
| Lifting speed | 15 m/min at 1. layer // 20 m/min at 5. layer |
|---------------|--|

| | |
|-----------------|--|
| Misc. equipment | Spooling device (adjustable for 0-90° wire out direction at horizontal. Max fleet angle is 5°) |
|-----------------|--|

| | |
|------------|-------------------------------------|
| Drive mode | Available as normal winch (lifting) |
|------------|-------------------------------------|

MECHANICAL

| | |
|---------------------|--------------------|
| Size L x W x H (mm) | 2188 x 2000 x 1800 |
|---------------------|--------------------|

| | |
|-------------|--|
| Weight (kg) | 4000 kg including spooling device. Weight of wire rope are not included. |
|-------------|--|

| | |
|------------------------|-------------------------------|
| Lifting lugs installed | Yes, included beam and sling. |
|------------------------|-------------------------------|

| | |
|--------------------|---|
| Wire rope capacity | 5 layers with wire rope Ø29 mm - max 300 meter. |
|--------------------|---|

Kolos is a leading supplier for lifting operations.

We have drum and linear winches in various sizes, available with constant tension and active heave system.



sales@kolos.no // [+47 98 90 44 44](tel:+4798904444)